


FONDI PER TUBI

PIPE ENDS

Acciaio Inox 304 L - 316 L

Stainless Steels 304L - 316L



POLLICI INCH	DN ND	Ø D mm	H mm	R mm	r mm	h mm	S mm	kg per 1 mm spess. kg for 1 mm thick	Vol. litri/litres
1/2"	15	21,3	11	22	2,2	4	2	0,010	
3/4"	20	26,9	12	27	2,7	4	2	0,015	
1"	25	33,7	14	34	3,4	4	2	0,020	
1" ¼	32	42,4	16	42	4,2	4	2	0,030	
		44,5	16	44	4,4	4	2	0,030	
1" ½	40	48,3	18	48	4,8	4	2	0,035	
		54,0	18	54	5,4	4	2	0,035	
2"	50	60,3	20	60	6,0	6	2 - 3	0,040	
		70	24	70	7,0	10	3	0,050	
2" ½	65	76,1	25	76	7,6	8	2 - 3	0,060	
3"	80	88,9	26	89	8,9	8	2 - 3	0,080	
3" ½		101,6	28	101	10,1	8	2 - 3	0,100	
		108	28	108	10,8	8	2 - 3	0,120	
4"	100	114,3	30	114	11,4	8	2 - 3	0,150	
		129	32	129	12,9	10	2 - 3	0,160	
		133	34	133	13,3	10	2 - 3	0,180	
5"	125	139,7	36	140	14,0	10	2 - 3	0,200	0,6
		154	40	159	15,9	10	2 - 3	0,300	0,8
6"	150	168,3	45	168	16,8	12	2-3-4-5	0,350	0,9
		193,7	46	194	19,4	12	3-4-5	0,420	1,5
		204,0	48	204	20,4	12	3-4-5	0,425	1,6
8"	200	219,1	50	219	21,9	15	3-4-5-6	0,600	2,0
		244,5	60	244	24,4	18	3-4-5-6	0,800	2,5
10"	250	273	70	273	27,3	18	3-4-5-6	1,000	4,0
12"	300	323,9	80	324	32,4	20	3-4-5-6	1,300	7,0
14"	350	355,6	90	355	35,6	20	3-4-5-6	1,400	9,0
16"	400	406,4	100	406	40,6	30	3-4-5-6	1,800	12,0
	450	457,2	110	458	45,8	30	3-4-5-6	2,100	14,0
20"	500	508	120	508	50,8	30	3-4-5-6	2,400	16,0

*A richiesta si eseguono
fondi ellittici*

*For Caps with different
forms upon request*

TOLLERANZE/TOLERANCES			
D mm	S mm	H ÷ h mm	R ÷ r mm
± 0,5 %	± 12,5 %	± 3	± 10 %