


FONDI PER TUBI

PIPE ENDS

Acciaio Carbonio S235JR - P265GH

Carbon Steel S235JR - P265GH



POLLICI INCH	∅ D mm	H mm	R mm	r mm	h mm	S mm	kg per 1 mm spess. kg for 1 mm thick	Vol. litri/litres
1/2"	21,3	10	22	2,2	4	3	0,010	
3/4"	26,9	10	27	2,7	4	3	0,015	<i>A richiesta fondi ellittici o di forma diversa</i>
1"	33,7	15	34	3,4	6	3	0,020	
1" ¼	42,4	19	42	4,2	8	3	0,030	<i>For Caps with different forms upon request</i>
1" ½	48,3	21	48	4,8	8	3	0,035	
	57	21	57	5,7	8	3	0,035	
2"	60,3	22	60	6,0	10	3	0,040	
	70	22	70	7,0	10	3	0,050	
2" ½	76,1	26	76	7,6	12	3	0,060	
3"	88,9	28	89	8,9	14	3 - 4	0,080	
3" ½	101,6	30	101	10,1	15	3 - 4	0,100	
	108	32	108	10,8	15	3 - 4	0,120	
4"	114,3	40	114	11,4	16	3 - 4	0,150	
	133	40	133	13,3	18	3 - 4	0,180	
5"	139,7	42	140	14,0	18	3 - 4	0,200	0,6
	159	48	159	15,9	20	3-4-5	0,300	0,8
6"	168,3	52	168	16,8	20	3-4-5	0,350	0,9
	193,7	68	194	19,4	25	3-4-5	0,420	1,5
8"	219,1	72	219	21,9	30	3-4-5-6	0,600	2,0
	244,5	90	244	24,4	30	3-4-5-6	0,800	3,2
10"	273	100	273	27,3	30	3-4-5-6	1,000	4,0
12"	323,9	105	324	32,4	30	3-4-5-6	1,300	7,0
14"	355,6	110	355	35,6	35	3-4-5-6	1,400	9,0
	368	110	368	36,8	35	4-5-6-8	1,500	10,0
16"	406,4	115	406	40,6	40	5-6-8	1,800	12,0
	419	120	419	41,9	40	5-6-8	2,000	14,0

TOLLERANZE/TOLERANCES			
D mm	S mm	H - h mm	R - r mm
± 0,5 %	± 12,5 %	± 3	± 10 %